

Fluid-Applied Traffic Coating Systems

Comprehensive Solutions for Pedestrian, Vehicular and Specialty Applications



CONNECTIONS: THE KEY TO LONG-TERM SUCCESS A Single Source for a Superior Solution

When it comes to protecting the entire building envelope, Tremco stands alone as your single source manufacturer of choice. On-site training, field support, and sustainable solutions designed to streamline your design and installation process are only a few of the value-added solutions we provide. Our team is adept at resolving numerous building envelope challenges that you may encounter on the job — and we pride ourselves on helping your team realize the maximum long-term value and quality of your finished structure.

Tremco products are conceived, formulated and tested in our labs, as well as in the field to ensure maximum compatibility and connectivity. Our expertise extends to all six sides of the building envelope, providing peace of mind. You are always covered when your project abuts, adjoins or overlaps other Tremco components or systems, effectively eliminating these otherwise troublesome connection points. Few others can offer this type of comprehensive approach.

Ultimately, our attention to these connections allows us to provide unique, all-inclusive system warranty options that our competitors simply cannot match.

Proven Performance

Tremco traffic coating products and systems are built upon a four decade track record of proven long-term performance. These systems have been independently tested to ensure they will meet the complex installation scenarios and grueling service condition demands of your project.



TRAFFIC COATINGS OVERVIEW Pedestrian | Vehicular | Specialty

With a wide range of solutions for vehicular, pedestrian and specialty applications, Tremco's highperformance liquid-applied membranes offer superior, long-term durability in traffic-bearing service conditions.

Our systems are designed to waterproof structures, protecting substrates from the harsh effects of chemical intrusion, thereby extending the lifecycle of these surfaces. The waterproofing layer of our systems are protected by various wear and top coats, increasing the durability of the installed system.

With over 40 years of experience in traffic coatings, we've created and developed products that meet the unique demands of any project. Our coatings portfolio addresses speed of application, durability, budget considerations and more. We also offer Neighbor Friendly (NF) formulas for sensitive area applications and a fully-compatible range of detailing sealants.

Whether repair/restoration or new construction, Tremco has proven solutions for the following applications:

- Parking garages
- Stadiums
- Dumpster areas
- Pedestrian walkways
- Mechanical rooms
- Hardscape/pool areas
- Balconies
- Recreation decks

On-Site Training, Testing, and Tech Support


On-site conditions always vary, presenting challenges on the project. Tremco's local technical sales representatives work with installers to provide the ideal solution. Immediate assistance is always available by calling our Technical Services Department.

APPLICATIONS:

			&	ian Deck venicu	allect http://	t Sufface Root P	ane	anical Room
	PHMOG	d under T	re pedes	ut vehici	ia. Athleti	i Suface Root P	Mecho	stite B
PRIMERS								
Vulkem® Primer #171 [‡]	•	•	٠	•	•	•	•	•
Vulkem [®] Primer #191 QD	•	•	•	•	•	•		•
Tremco Epoxy Primer	•	•	٠	•	•	•	•	•
TREMprime [®] Multi- Surface Urethane Primer	•		•				•	•
BASE COATS								
Vulkem® 350	•	•	٠	•	•	•	•	•
Vulkem [®] 350NF	•	•	•	•	•	•	•	•
Vulkem [®] 360NF	•		•	•	•	•	•	•
NTERMEDIATE COATS								
Vulkem [®] 345				•				
Vulkem [®] 346				•				
Vulkem [®] 351								
Vulkem [®] 351NF	•							
Vulkem [®] 950NF				•			•	
OP COATS								
Vulkem [®] 346				•				
Vulkem® 351			•		•	•	•	•
Vulkem [®] 351NF	•		•		•	•	•	•
Vulkem [®] 950NF			•	•			•	
Vulkem [®] 951NF	•		•	•	•	•	•	•
PECIALTY								
Vulkem® 0C810	•		•			•	•	•

Reference the current product data sheets on our website at www.tremcosealants.com for more specific product information. For specific tie-in recommendations and Instructions, please contact your local Tremco Sales or Technical Service Representative. *Not for use in Canada

PROPERTIES:



Recommended Substrates:

PRIMERS				
Vulkem® Primer #171 [‡]		1		Concrete, plywood, other porous substrates**
Vulkem [®] Primer #191 QD	•	1		Concrete, plywood, other porous substrates**, interlaminary, uretha coatings, TREMproof membranes
Tremco Epoxy Primer		2		Concrete, plywood, other porous substrates**, interlaminary, uretha coatings, TREMproof membranes
TREMprime® Multi- Surface Urethane Primer	•	2		Concrete, plywood, other porous substrates**, interlaminary, ur thane coatings
BASE COATS				
Vulkem® 350		1		Concrete, metal
Vulkem®350NF	٠	1		Concrete, metal
Vulkem®360NF	٠	2		Concrete, metal
INTERMEDIATE COATS				
Vulkem® 345		2		Vulkem 350
Vulkem® 346		1	•	Vulkem 345
Vulkem® 351		1	•	Vulkem 350, 350NF, 360NF
Vulkem®351NF		2	•	Vulkem 350NF
Vulkem [®] 950NF	•	2		Vulkem 350NF
TOP COATS				
Vulkem® 346		1	•	Vulkem 345
Vulkem® 351		1	•	Vulkem 350, 350NF, 360NF
Vulkem® 351NF	•	2	•	Vulkem 350NF
Vulkem [®] 950NF	•	2		Vulkem 350NF
Vulkem® 951NF	•	2	•	Vulkem 950NF
SPECIALTY				
Vulkem® 0C810	•	1		Concrete, wood (with Tremco-approved primer)

Reference the current product data sheets on our website at www.tremcosealants.com for more specific product information.

For specific tie-in recommendations and Instructions, please contact your local Tremco Sales or Technical Service Representative.

*Prior approval required by Tremco Technical Services; approval is based on compatibility and adhesion testing.


[‡]Not for use in Canada

PEDESTRIAN SYSTEMS

STANDARD PEDESTRIAN APPLICATIONS

Recommended two-coat systems for applications that will receive light-tomedium pedestrian traffic, such as balconies, mechanical rooms, walkways and terraces.

	Pr	oduct Options	Coverage Rate	Wet Mils	
	ţ	Vulkem 350	40 to 64 ft²/gal	25 to 40	
-	Base Coats	Vulkem 350NF	64 ft²/gal	25	
	Bas	Vulkem 360NF	64 ft²/gal	25	
		Vulkem 351	105 ft²/gal	15	
	Top Coats	Vulkem 351NF	105 ft²/gal	15	
	Top (Vulkem 950NF	133 ft²/gal	12	
		Vulkem 951NF	133 ft²/gal	12	



Typical Systems

Standard: 350NF / 351 Low VOC: 350NF / 351NF Quick-Cure, Low VOC: 360NF / 951NF

Contact your local Tremco Sales Representative to determine the highest-performing system based on regional needs.



Ideal for plazas, recreation decks, balconies, pool decks, mechanical rooms, stadiums, athletic surfaces and similar applications requiring an elastomeric waterproofing system.

HEAVY-DUTY PEDESTRIAN APPLICATIONS

Recommended three-coat systems for areas that will be exposed to steady foot traffic, such as stadiums, amenity decks and pedestrian bridges.

Pr	oduct Options	Coverage Rate	Wet Mils
ts	Vulkem 350	40 to 64 ft²/gal	25 to 40
Base Coats	Vulkem 350NF	64 ft²/gal	25 to 40
Bä	Vulkem 360NF	64 ft²/gal	25 to 40
iate	Vulkem 351	105 ft²/gal	15
Intermediate	Vulkem 351NF	105 ft²/gal	15
Inte	Vulkem 950NF	133 ft²/gal	12
	Vulkem 351	105 ft²/gal	15
Top Coats	Vulkem 351NF	105 ft²/gal	15
Тор (Vulkem 950NF	133 ft²/gal	12
	Vulkem 951NF	133 ft²/gal	12

Typical Systems


Standard: 350NF / 351 / 351 Quick-Cure, Low VOC: 360NF / 951NF / 951NF

Contact your local Tremco Sales Representative to determine the highest-performing system based on regional needs.

VEHICULAR SYSTEMS

STANDARD VEHICULAR APPLICATIONS

Recommended three-coat systems for areas that will be exposed to vehicular traffic.



	Pr	oduct Options	Coverage Rate	Wet Mils	
	ş	Vulkem 350	40 to 64 ft²/gal	25	
-	Base Coats	Vulkem 350NF	64 ft²/gal	25	
	Bas	Vulkem 360NF	64 ft²/gal	25	
	iate	Vulkem 345	105 ft²/gal	15	
	Intermediate	Vulkem 346	105 ft²/gal	15	
	Inte	Vulkem 950NF	133 ft²/gal	12	
	ts	Vulkem 346	133 to 160 ft²/gal	10 to 12	
	Top Coats	Vulkem 950NF	133 ft²/gal	12	
	P	Vulkem 951NF	133 ft²/gal	12	

Typical Systems

Standard: 350NF / 345 / 346, 350NF / 346 / 346 Low VOC, Indoor: 350NF / 950NF / 950NF Low VOC, UV Stable: 350NF / 950NF / 951NF

Vulkem 360NF can be used as a quick-cure, or low-temperature option.

Contact your local Tremco Sales Representative to determine the highest-performing system based on regional needs.



Ideal for waterproofing concrete slabs and protecting occupied areas underneath from water damage while protecting the concrete from the damaging effects of water, deicing salts, chemicals, gasoline, oils and anti-freeze.

HEAVY-DUTY VEHICULAR APPLICATIONS

Recommended four-coat systems for areas that will be subjected to steady vehicular traffic.

Pr	oduct Options	Coverage Rate	Wet Mils	
ts	Vulkem 350	40 to 64 ft²/gal	25	
Base Coats	Vulkem 350NF	64 ft²/gal	25	
Bas	Vulkem 360NF	64 ft²/gal	25	
iate	Vulkem 345	105 ft²/gal	15	
Intermediate	Vulkem 346	105 ft²/gal	15	
Inte	Vulkem 950NF	133 ft²/gal	12	
ts	Vulkem 346	133 to 160 ft²/gal	10 to 12	
Top Coats	Vulkem 950NF	133 ft²/gal	12	
P	Vulkem 951NF	133 ft²/gal	12	

Typical Systems

Standard: 350NF / 345 / 345 / 346, 350NF / 346 / 346 / 346 Low VOC, Indoor: 350NF / 950NF / 950NF / 950NF Low VOC, UV Stable: 350NF / 950NF / 950NF / 951NF

Vulkem 360NF can be used as a quick-cure, or low-temperature option.

Contact your local Tremco Sales Representative to determine the highest-performing system based on regional needs.



SPECIALTY SYSTEMS

BALCONY, LIGHT PEDESTRIAN & MECHANICAL ROOM APPLICATIONS

Recommended one-coat systems for areas that will receive light foot traffic such as balconies and mechanical rooms / work areas.

Pro	oduct Options	Coverage Rate	Wet Mils	
	Vulkem Primer #171	100 to 600 ft²/gal		
Primer	Vulkem Primer #191 QD	400 to 450 ft²/gal		
Δ.	TREMprime Multi-Surface Urethane Primer	200 to 300 ft²/gal		
Top	Vulkem 0C810	64 ft²/gal	25	

UNDER-TILE APPLICATIONS

Recommended two-coat system for tiles, pavers and bonded overburden.

Pro	oduct Options	Coverage Rate	Wet Mils	-
Base	Vulkem 350NF	25 to 40 ft²/gal	40 to 60	
Top	Tremco Epoxy Primer	133 to 160 ft²/gal	10 to 12	

Waterproof coatings for a variety of specialty applications, including one-coat and rapid-cure solutions, as well as systems for under-tile applications, mechanical rooms and areas subject to heavy abrasion.

MECHANICAL ROOM APPLICATIONS

Recommended two-coat systems for mechanical rooms / work areas.

Pro	oduct Options	Coverage Rate	Wet Mils
ts	Vulkem 350	40 to 64 ft²/gal	25 to 40
Base Coats	Vulkem 350NF	64 ft²/gal	25 to 40
Bas	Vulkem 360NF	64 ft²/gal	25 to 40
	Vulkem 351	105 ft²/gal	15
oats	Vulkem 351NF	105 ft²/gal	15
Top Coats	Vulkem 950NF	133 ft²/gal	12
	Vulkem 951NF	133 ft²/gal	12

Typical Systems

Standard: 350NF / 351 Low VOC: 350NF / 351NF Low VOC, Quick-Cure: 360NF / 950NF

Contact your local Tremco Sales Representative to determine the highest-performing system based on regional needs.

VULKEM[®] EWS WITH PUMA TECHNOLOGY FOR EXTREME-WEARING SYSTEMS

Recommended systems for areas subject to heavy abrasion, such as loading docks, dumpster storage areas, ticket splitters and helical ramps, including a variety of specialty applications.

Vulkem EWS Coating Systems with PUMA technology provide superior elongation over traditional MMA/PMMA technology systems. These rapid-curing systems feature extreme durability, fast cure independent of low temperatures, crack bridging, tenacious adhesion and superior abrasion resistance.

For complete details and Vulkem EWS System offerings, please refer to the PUMA Technology brochure available on our website, or request a copy from your local Tremco Sales Representative.



(Vehicular System Shown)



220 Wicksteed Avenue, Toronto, ON M4H 1G7 Phone: 416.421.3<u>300 • 800.363.3213</u>

www.tremcosealants.com